



ATLAS
Carpet Tiles



Atlas 01





Atlas 02



Atlas 03




Atlas 04




Atlas 05







Atlas 01




Atlas 02



Atlas 03



Atlas 04



Atlas 05

SPECIFICATION:

Face yarn:	100% Nylon
Dye method:	100% Solution dyed
Gauge:	1/12
Pile weight:	500g/m ² (±5%)
Total weight:	4100g/m ² (±5%)
Pile height:	4mm (±0.5mm)
Total height:	6mm (±0.5mm)
Backing:	PVC
Size:	50cmx50cm
Dimensional stability:	≤0.2%
Packaging box:	24 tiles/6m ²

PERFORMANCE

Classification:	33
Castor chair rating:	A: intensive use
Fire classification :	Class 1 (ASTM E648)
Soil resistance :	2-3 grade ISO11378-2: 2001
Impact sound insulation:	ΔL _w :26 dB
Sound absorbtion:	Frequency Hz:125 250 500 1000 2000 4000 α _s 0.01 0.05 0.08 0.22 0.34 0.44
Noise reduction:	α _w : 0.20
Colour fastness to light:	5 grade QB/T 2755-2005
Colour fastness to water:	4-5 grade QB/T 2755-2005
Rubbing fastness:	4-5 grade QB/T 2755-2005
Indoor air quality: (GB18587-2001 A grade)	TVOC ≤0.500mg/m ³ h Formaldehyde≤ 0.050mg/m ³ h Styrene≤ 0.400mg/m ³ h 4-phenylcyclohexene≤ 0.050mg/m ³ h

